



DELTA SW4

DN25 - DN150 (1" - 6")

Based on more than 50 years' experience in valve production APV has developed the DELTA SW4 hygienic single seat valve: a modern, highly versatile single seat valve, which does not only fulfil the demands of today's process industry but also a great deal of tomorrow's.

Installing the DELTA SW4 valves is an investment in efficiency, production flexibility or in other words: in the future. When designing this valve great emphasis has been put on facilitating valve handling, installation and maintenance.

Characteristics

Its hygienic design makes it ideal for applications in the dairy, beverage and brewing industries, as well as the chemical and pharmaceutical industries.

The valve is EHEDG approved and it is available in on/off and change-over versions. The valve can also be supplied in 3A approved design.

Features & benefits

Sturdy ball shaped housing designed for optimum cleanability. The extra wall thickness of the valve housing minimises stresses in the seat area. At the same time the ball shaped housing effectively prevents sump or dome, thus optimising valve cleanability and reducing CIP-time. A comprehensive range of valve housings are available to cover any requests.

Controlled compression of seat seal

The metallic stop ensures defined compression of seat area and minimises stress and load on seat seals, which in the long run minimises downtime. Furthermore, this arrangement ensures smooth product transition in this area. Wear resistant elastomer/PTFE shaft seal and shaft bearing arrangement increases seal lifetime and consequently minimises maintenance costs and general downtime.

Installation and maintenance convenience

- A handy clamp closure system or a few bolts (DN125-150 and 6") between housing and yoke provides quick and easy access to product-wetted parts. The housings (DN25-100 and 1" - 4") may be orientated in various directions to ensure multiple installation possibilities.
- Moulded elastomer profile seals with clear identification markings ensure prompt and failsafe identification of seals during maintenance.
- Only one hexagonal nut outside the product area ensures quick and easy service of the valve.
- Different actuator sizes are available, and for DN25-100 these are interchangeable. This means that different product pressures can be handled.
- Actuator design prepared for NC/NO (Normally closed / normally open).
- Despite the thick-walled housing the valve is very low weight.
- Maintenance-free actuator, covered by the 5-year APV guarantee.

Control Units

The DELTA SW4 valves can be delivered with a comprehensive range of DELTA CU control units. The DELTA CU are electrically provided to connect direct to a PLC system (DELTA CU Direct connect). Optional to support fieldbus protocols like AS-i, Profibus and DeviceNet.

Options for DELTA SW4

In order to handle every inquiry the following options are available:

- Stroke limiter (DN25-100 and 1" - 4")
- Crank handle for manual operation (DN25-150 and 1" - 6")
- Oil damp cylindre (DN25-100 and 1" - 4")
- Steam barrier
- Long stroke (DN50-100 and 2" - 4")
- Tangential inlet (1" - 4" imperial sizes only)
- Proximity holder
- Tank outlet version
- 3.1 certificate
- 3A version



DELTA SW4
DN25-150 (1" - 6")



DELTA SWmini4
DN10-20 (1/2" - 1")
(See separate data sheet)

Technical data

Sizes	DN25 - DN150 (1" - 6")
Product wetted parts	AISI 316L
Non-product wetted parts	AISI 304
Seal materials	Standard EPDM/PTFE Optional VMQ, FPM and HNBR
Max. temperature	EPDM / HNBR 135°C (short time 140°C) VMQ 135°C not to be used for hot water FPM 135°C not to be used for steam
Max. line pressure	10 bar
Min. control air pressure	6 bar
Max. control air pressure	8 bar

SPX[®]
WHERE IDEAS MEET INDUSTRY

Your local contact



APV, An SPX Brand
Zechenstrasse 49,
D-59425 Unna, Germany
Phone: +49(0) 23 03/ 108-0 Fax: +49(0) 23 03 /108-210

For more information about our worldwide locations, approvals, certifications, and local representatives, please visit www.apv.com. SPX Corporation reserves the right to incorporate our latest design and material changes without notice or obligation. Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing.

Issued: 11/2009 8007-02-11-2009-GB

Copyright © 2004, 2009 SPX Corporation